

TOP SELLER

Voyager II® Pop-Up Gear Drive Head— The #1 Selling Gear Drive

Produces a quiet and smooth rotating spray
Universal—Works with or as a replacement
for impact or gear drive sprinklers
(Including Hunter®, Rainbird® and Toro®)

Ideal for large areas

Easy to Adjust Spray Distance—
25' - 40' radius

Full or Part Circle—40° - 360°

Large Filter—Reducing clogged nozzles

Includes adjustment tool, installed nozzle

55060 Clam

55061 Display Box

55067 Canister Replacement Head

Operation Range:

Precipitation Rate:

Approximately .4" per hour at 50 psi for
spacings 25' to 45'

Radius:

25' to 40'

Pressure Range:

30 to 70 psi

Flow:

.5 to 14.4 gpm

Specifications:

3/4" FNPT bottom inlet

Nozzle outlet trajectory is 25° standard or
13° low angle

Dimensions:

Overall height:

55060 & 55061 7-3/8"

Exposed Surface Diameter:

All:

1-3/4"

Pop-Up height:

55060 & 55061, 4"

Voyager II® Gear Drive

gpm / Nozzle

Standard
Nozzles

	30	40	50	60	70
1	0.5	0.6	0.7	0.8	—
2	0.7	0.8	0.9	1.0	—
3	0.9	1.0	1.2	1.3	—
4	1.2	1.4	1.6	1.8	—
5	1.6	1.8	2.0	2.2	—
6	2.0	2.4	2.7	2.9	—
7[†]	2.6	3.0	3.4	3.7	—
8	3.2	3.7	4.2	4.6	—
9	4.2	4.9	5.5	6.0	—
10	—	6.0	6.8	7.6	8.2
11	—	8.0	8.9	9.8	10.5
12	—	11.4	12.2	13.2	14.4

Spacing: 20' - 45'

[†] Factory installed #7 nozzle